

leanwork STATION

Technical features



Laser (optional)

- high-performance 130 mW laser diode
- class 3B with 650 nm wavelength
- displays spot points, texts or free form graphics
- two-dimensional display of the assembly position(s) to be processed
- simple modification of the display positions via software



Mounting Workstation

- all metal parts are conductive powder-coated
- table plate with sturdy hard laminate covering
- working surface loadable up to 200 kg with evenly distributed load
- height adjustment range from 740 mm to 1040 mm
- also available with electrical height adjustment option



Operator Information System

- simple acquisition of operating data (quantities, times/MTM, quality and improvement measurements) via a single user interface
- order data acceptance from the ERP and, where required, enhancement with additional relevant production data
- stand-alone or server solution
- paperless workstation by integration of work instructions, rules, etc. on multimedia-based format
- freely customisable surface thanks to ergonomic design



Pick-to-Light System

- two-digit 7 segment display to indicate the quantity to be picked
- two indicator LEDs, including one multicolour design for compartment marking
- robust metal acknowledgement push button for picking confirmation
- two membrane "+/-" keys e.g. for value correction and "up/down" position indication
- solid aluminium design;
display size: 80 x 30 x 27 mm (w x h x d)



Exclusive distributor
for Belgium & Luxemburg

MULTIPROX N.V.
Lion d'Orweg 12
B-9300 Aalst

T +32 (0)53 766 566
F +32 (0)53 78 39 77

mail@multiprox.be
www.multiprox.be